

PJ

Smallest Physical Size

DESIGN FEATURES

- High energy efficiency
- One-piece, compact construction
- No whirl vanes or internal parts
- 1/8" or 1/4" male connection
- 100-mesh screen, 10 micron paper filter or polypropylene filter optional

SPRAY CHARACTERISTICS

- Finest fog of any direct pressure nozzle
- Produces high percentage of droplets under 50 microns


Spray pattern: Cone-shaped Fog

Spray angle: 90°. For best 90° pattern operate nozzle at or above 4 bar


Flow rates: 0.043 to 5.34 l/min



Metal




Fog



Male



Fog Pattern



PJ with polypropylene filter

Dimensions are approximate. Check with BETE for critical dimension applications.

PJ Flow Rates and Dimensions

Impingement, 90° Spray Angle, 1/8" or 1/4" Pipe Sizes, BSP or NPT

Male Pipe Size	Nozzle Number	K Factor	LITERS PER MINUTE @ BAR								Approx.			Pipe Size	Dim. (mm)		Wt. (g) Metal
			2 bar	3 bar	5 bar	10 bar	20 bar	30 bar	50 bar	70 bar	Approx.	Approx.	Spray				
											Orifice Dia. (mm)	Cov. D (mm)	Height H (mm)				
1/8	PJ6	0.0137			0.031	0.043	0.061	0.075	0.097	0.114	0.152	203	103	1/8	19.1	11.1	7
	PJ8	0.0259			0.058	0.082	0.116	0.142	0.183	0.217	0.203	254	127				
	PJ10	0.0387		0.067	0.087	0.123	0.173	0.212	0.274	0.324	0.254	254	127				
	PJ12	0.0524		0.091	0.117	0.166	0.234	0.287	0.371	0.439	0.305	254	127				
	PJ15	0.0843	0.119	0.146	0.189	0.267	0.377	0.462	0.596	0.705	0.381	254	127				
OR	PJ20	0.153	0.216	0.264	0.341	0.483	0.683	0.836	1.08	1.28	0.508	310	155	1/4	24.6	14.2	
	PJ24	0.228	0.322	0.395	0.510	0.721	1.02	1.25	1.61	1.91	0.610	400	200				
	PJ28	0.296	0.419	0.513	0.662	0.937	1.32	1.62	2.09	2.48	0.711	460	230				
1/4	PJ32	0.410	0.580	0.710	0.917	1.297	1.83	2.25	2.90	3.43	0.813	560	280				
	PJ40	0.638	0.902	1.11	1.43	2.02	2.85	3.49	4.51	5.34	1.02	610	305				

$$\text{Flow Rate (l/min)} = K \sqrt{\text{bar}}$$

Standard Materials: Brass, 303 Stainless Steel and 316 Stainless Steel.

Spray angle performance varies with pressure. Contact BETE for specific data on critical applications.



MISTING

Call for the name of your nearest BETE representative.

CALL 413-772-0846